4

Motor Control Center (MCC) with DIN Rail Industrial Patch Panel Mounted in Pathway, Enabling Ethernet Devices Across Multiple Sections

2

3

To Zone / $\ensuremath{\mathsf{IDF}}$ / $\ensuremath{\mathsf{MDC}}$, see separate pages for more.



D


С

В

Α



- MCC's were Ethernet-enabled by means of industrial switches.
- Due to the high noise and voltage environment of the MCC, Panduit presents the industrial DIN railmounted 8 port patch panel assembled with two loomed preterminated cable bundles.
- This innovative solution removes the consideration for noise and voltage by centrally locating the switch in an Integrated Network Zone System, Industrial Distribution Frame or Micro Data center and enables a structured infrastructure deployment.



4

3

2

1


1


D


С

В

Α







Bill of Materials

| Motor Control Center I4JPBJLU* Category 6A, plenum motor control center cabling bundle system I4KOTJLUX* Category 6A, outdoor motor control center cabling bundle system CDPP8RG IndustrialNet, 8-port DIN rail mount patch panel. Includes screws to attach faceplate and Ultimate ID labels and clear label covers. Mini-Com DIN Rail Mount Adapter mounts to standard 35mm DIN rail and accepts any single port Mini-Com Module, international gray. Includes a label and label cover. CADIN1IG rail and accepts any single port Mini-Com Module, international gray. Includes a label and label cover. SFCH6X04ATL-UG Copper Cable, Industrial, Cat 6A 4-pair, 24/7 AWG Stranded, SF/UTP, CMR, 600V rated, Oil Res., UV Res., Tea FOPPX12Y 50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibers ISTPHCH2MTL Patch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter. CJS6X88TGY Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield. J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max bundle capacity, nylon 6.6 with metal attachments, black. WG12BL10 12* W x10' L Wyr-Grid pathway section Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distributi | PartNumber | Description | |
|--|---|--|--|
| I4KOTJLUX* Category 6A, outdoor motor control center cabling bundle system CDPP8RG IndustrialNet, 8-port DIN rail mount patch panel. Includes screws to attach faceplate and Ultimate ID labels and clear label covers. Mini-Com DIN Rail Mount Adapter mounts to standard 35mm DIN rail and accepts any single port Mini-Com Module, international gray. Includes a label and label cover. CADIN1IG rail and accepts any single port Mini-Com Module, international gray. Includes a label and label cover. CSFCH6X04ATL-UG Copper Cable, Industrial, Cat 6A 4-pair, 24/7 AWG Stranded, SF/UTP, CMR, 600V rated, Oil Res., UV Res., Tea Cabling, Connectors and Pathways 50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibers FOPPX12Y S0um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibers ISTPHCH2MTL Patch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter. CJS6X88TGY Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield. J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max bundle capacity, nylon 6.6 with metal attachments, black. WG12BL10 12" W x 10' L Wyr-Grid pathway section HLB2S-C0 Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Cen | Motor Control Center | | |
| CDPP8RG IndustrialNet, 8-port DIN rail mount patch panel. Includes screws to attach faceplate and Ultimate ID labels and clear label covers. Mini-Com DIN Rail Mount Adapter mounts to standard 35mm DIN rail and accepts any single port Mini-Com Module, international gray. Includes a label and label cover. ISFCH6X04ATL-UG Copper Cable, Industrial, Cat 6A 4-pair, 24/7 AWG Stranded, SF/UTP, CMR, 600V rated, Oil Res., UV Res., Tea Cabling, Connectors and Pathways 50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibers FOPPX12Y 50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibers ISTPHCH2MTL Patch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter. CJS6X88TGY Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield. J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black. WG12BL10 12" W x 10' L Wyr-Grid pathway section HLB2S-C0 Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Center Z23** Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adapt | I4JPBJLU* | Category 6A, plenum motor control center cabling bundle system | |
| CDPP8RGattach faceplate and Ultimate ID labels and clear label covers.CADIN1IGMini-Com DIN Rail Mount Adapter mounts to standard 35mm DIN rail and accepts any single port Mini-Com Module, international gray. Includes a label and label cover.ISFCH6X04ATL-UGCopper Cable, Industrial, Cat 6A 4-pair, 24/7 AWG Stranded, SF/UTP, CMR, 600V rated, Oil Res., UV Res., TeaFOPPX12Y50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibersFOPPX12YSoum OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibersISTPHCH2MTLPatch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter.CJS6X88TGYCategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.JP2SBC50-L20Ifanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackZ23**Pre-Configured Network Zone System, Industrial Distribution Center and Micro Data Center copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | I4KOTJLUX* | Category 6A, outdoor motor control center cabling bundle system | |
| attach faceplate and Ultimate ID labels and clear label covers. Mini-Com DIN Rail Mount Adapter mounts to standard 35mm DIN rail and accepts any single port Mini-Com Moule, international gray. Includes a label and label cover. ISFCH6X04ATL-UG Copper Cable, Industrial, Cat 6A 4-pair, 24/7 AWG Stranded, SF/UTP, CMR, 600V rated, Oil Res., UV Res., Tea Cabling, Connectors and Pathways FOPPX12Y 50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibers ISTPHCH2MTL Patch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter. CJS6X88TGY Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield. J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max bundle capacity, nylon 6.6 with metal attachments, black. WG12BL10 12" W x 10' L Wyr-Grid pathway section HLB2S-C0 Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Center Z23** Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels | CDPP8RG | | |
| CADIN1IG rail and accepts any single port Mini-Com Module, international gray. Includes a label and label cover. ISFCH6X04ATL-UG Copper Cable, Industrial, Cat 6A.4-pair, 24/7 AWG Stranded, SF/UTP, CMR, 600V rated, Oil Res., UV Res., Tea Cabling, Connectors and Pathways FOPPX12Y 50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibers ISTPHCH2MTL Patch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter. CJS6X88TGY Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield. J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black. WG12BL10 12" W x 10' L Wyr-Grid pathway section HLB2S-C0 Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Center Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-Configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. MDC**** network cabling, patch panels, cable management, grounding, | | • | |
| Includes a label and label cover.ISFCH6X04ATL-UGCopper Cable, Industrial, Cat 6A 4-pair, 24/7 AWG Stranded, SF/UTP, CMR, 600V rated, Oil Res., UV Res., TeaCabling, Connectors and PathwaysFOPPX12Y50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibersISTPHCH2MTLPatch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter.CJS6X88TGYCategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.JP2SBC50-L20J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial Distribution Center and Micro Data CenterZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC****Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | CADIN1IG | | |
| ISFCH6X04ATL-UGCopper Cable, Industrial, Cat 6A 4-pair, 24/7 AWG Stranded, SF/UTP, CMR, 600V rated, Oil Res., UV Res.,TeaCabling, Connectors and PathwaysFOPPX12Y50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibersISTPHCH2MTLPatch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter.CJS6X88TGYCategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.JP2SBC50-L20J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway section Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackZ23**Pre-Configured Network Zone System, Industrial Distribution Center and Micro Data Center enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC****network cabling, patch panels, cable management, grounding, | | | |
| ISPCH6X04AIL-UG SF/UTP, CMR, 600V rated, Oil Res., UV Res., Tea Cabling, Connectors and Pathways FOPPX12Y 50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibers ISTPHCH2MTL Patch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter. CJS6X88TGY Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield. JP2SBC50-L20 Ifanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black. WG12BL10 12" W x 10' L Wyr-Grid pathway section HLB2S-C0 Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Z23** Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. MDC**** Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | | |
| SF/UTP, CMR, 600V rated, Oil Res., UV Res., TeaCabling, Connectors and PathwaysFOPPX12Y50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibersISTPHCH2MTLPatch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter.CJS6X88TGYCategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield. J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackZ23**Pre-Configured Network Zone System, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC****Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | ISFCH6X04ATL-UG | | |
| FOPPX12Y50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um buffered fibersISTPHCH2MTLPatch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter.CJS6X88TGYCategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.JP2SBC50-L20flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC****network cabling, patch panels, cable management, grounding, | | SF/UTP, CMR, 600V rated, Oil Res., UV Res., Tea | |
| FOPPX12Ybuffered fibersISTPHCH2MTLPatch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter.CJS6X88TGYCategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.JP2SBC50-L20Gategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.JP2SBC50-L20flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackNetwork Zone System, Industrial Distribution Center and Micro Data CenterZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC***network cabling, patch panels, cable management, grounding, | Cabling, Connectors and Pathways | | |
| buffered fibersISTPHCH2MTLPatch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to RJ45 plug, teal, 2 meter.CJS6X88TGYCategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.JP2SBC50-L20J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC***network cabling, patch panels, cable management, grounding, | FOPPX12Y | 50um OM3 12 Fiber Indoor Armored Cable, Plenum (OFCP), 900um | |
| ISTPHCH2MIL RJ45 plug, teal, 2 meter. CJS6X88TGY Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield. J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black. WG12BL10 12" W x 10' L Wyr-Grid pathway section Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Center Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. MDC*** Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | buffered fibers | |
| RJ45 plug, teal, 2 meter.CJS6X88TGYCategory 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.JP2SBC50-L20J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackNetwork Zone System, Industrial Distribution Center and Micro Data CenterZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC***Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | ISTPHCH2MTL | Patch cord, IndustrialNet, category 5e, shielded, 600V, RJ45 plug to | |
| CJS6X881GYblack module with integral shield.J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackNetwork Zone System, Industrial Distribution Center and Micro Data CenterZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC****network cabling, patch panels, cable management, grounding, | | RJ45 plug, teal, 2 meter. | |
| black module with integral shield.JP2SBC50-L20J-Pro Cable support system, with screw-on beam clamp for use with flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackNetwork Zone System, Industrial Distribution Center and Micro Data CenterZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC****Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | CJS6X88TGY | Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded | |
| JP2SBC50-L20flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackNetwork Zone System, Industrial Distribution Center and Micro Data CenterZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC****Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | black module with integral shield. | |
| capacity, nylon 6.6 with metal attachments, black.WG12BL1012" W x 10' L Wyr-Grid pathway sectionHLB2S-C0Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, blackNetwork Zone System, Industrial Distribution Center and Micro Data CenterZ23**Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management.ZDF48-RAPre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches.MDC****Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | JP2SBC50-L20 | J-Pro Cable support system, with screw-on beam clamp for use with | |
| WG12BL10 12" W x 10' L Wyr-Grid pathway section HLB2S-C0 Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Center Z23** Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-configured Nicro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | flanges up to 1/2 (12.7mm) thick, 2.00 (50.8mm) max. bundle | |
| HLB2S-C0 Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Center Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. MDC**** Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | capacity, nylon 6.6 with metal attachments, black. | |
| HLB2S-C0 (19.1mm) width, nylon loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Center Z23** Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. MDC*** Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | WG12BL10 | | |
| (19.1mm) width, nyion loop, polyethylene hook, black Network Zone System, Industrial Distribution Center and Micro Data Center Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | HLB2S-C0 | Tak-Ty hook & loop stacked strip cable tie, 7.0 (178mm) length, 0.75 | |
| Z23** Pre-Configured Network Zone System, 24" x 36", mild steel enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-Configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | (19.1mm) width, nylon loop, polyethylene hook, black | |
| Z23** enclosure, for two industrial switches, includes (16) Cat 6 UTP copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. MDC*** Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | Network Zone System, Industrial Distribution Center and Micro Data Center | | |
| ZZ3*** copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. MDC**** Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | Z23** | Pre-Configured Network Zone System, 24" x 36", mild steel | |
| copper patch cords and jacks, (4) MM LC fiber patch cords with (6) adaptors, backplane and cable management. ZDF48-RA Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | enclosure, for two industrial switches, includes (16) Cat 6 UTP | |
| ZDF48-RA Pre-configured Industrial Distribution Frame enclosure ready for two access and two distribution switches. Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | copper patch cords and jacks, (4) MM LC fiber patch cords with (6) | |
| ZDF48-RA access and two distribution switches. Pre-Configured Micro Data Center, includes two side panels, network cabling, patch panels, cable management, grounding, | | adaptors, backplane and cable management. | |
| access and two distribution switches. Pre-Configured Micro Data Center, includes two side panels, MDC*** network cabling, patch panels, cable management, grounding, | ZDF48-RA | Pre-configured Industrial Distribution Frame enclosure ready for two | |
| MDC*** network cabling, patch panels, cable management, grounding, | | access and two distribution switches. | |
| | MDC*** | Pre-Configured Micro Data Center, includes two side panels, | |
| casters, shock pallet and ramp. | | network cabling, patch panels, cable management, grounding, | |
| | | casters, shock pallet and ramp. | |

*Motor Control Center Cable Bundles available in a variety of loom options, termination ends and overwrap options.

**Network Zone Enclosures available in mild steel, stainless steel or sloped versions and various levels of integration.

***Micro Data Centers available in 24 and 42 RU versions with various add-on kits.

For an expanded product offering visit panduit.com/networkpartsamerica or the online catalog at panduit.com.

About this Configuration


Before the advent of optimized network architectures, Motor Control Centers (MCCs) were standalone enclosures. Now with the Internet of Things growing faster than ever, industrial equipment needs to be connected in a robust and smarter way. With Panduit, the deployment of this architecture becomes much easier. From shielded cable and connectivity to cable management and grounding solutions; Panduit has all the products needed to make your industrial network more secure and future ready.

Industrial Distribution Frame

Using rack mount access switches, an IDF is intended for high-density industrial star networks that are connected to numerous HMIs, PLCs, Drives, or I/O blocks in harsh environments to keep traffic local. An IDF can also house distribution switches to efficiently route traffic between access switches that are often DIN-mounted switches in a control panel.

Purpose

The MCC is a poor location for low voltage switching devices due to the noise created by high current and voltage found in an MCC. Panduit's IndustrialNet 8-Port Din Rail patch panel allows you to replace the switch and remove these considerations while maintaining a structured cabling topology in your MCC deployment.



For more information contact your local distributor, Panduit Sales Representative, or the Panduit Industrial Network Infrastructure team at networkinfrastructure@panduit.com.