


## technical information

Panduit™ Opti-Core™ Fiber Optic Indoor Cable is an integral part of the Panduit end-to-end fiber optic solution, designed to support today's data needs while meeting tomorrow's ever-advancing network requirements. Standard RoHS compliant singlemode and multimode indoor cable is available in fiber counts from 2 to 48 fibers. 2 and 4-fiber interconnect cable is used within buildings to extend or interconnect network segments. The small cable size allows for installation in space-restricted areas for applications that include horizontal cabling systems in support of high-end workstations, secure networks, and zone cabling. Interconnect cable can also be used for patch cords and jumpers. 6 thru 48-fiber distribution cable is used within buildings to provide high-density connectivity and ease of installation. Applications include intra-building backbones, routing between telecommunications rooms, and connectorized cables in riser and low smoke zero halogen environments. Distribution cable in 6 and 12-fiber designs have 900µm tight-buffered fibers surrounded by aramid yarn strength members. Larger distribution cables (24 fibers and greater) feature a sub-unit design that simplifies fiber identification, provides easy access and routing of the fibers and increases cable durability with a dielectric central strength member. Opti-Core™ Fiber Optic Indoor Cable features the highest quality OM3 laser optimized fiber to support 10 Gb/s applications while maintaining compatibility with existing 50µm multimode systems. Fiber Optic Indoor Cable includes 300 OM3 Cable for 300 meter reach requirements and OM4 Cable for 550 meter reach requirements. 150 OM2+ Cable for 150 meter reach requirements and OM4 Cable for 550 meter reach requirements.



## application

For indoor use in intrabuilding backbone and horizontal installations.

## standards

IEC 60754-2 UL1666	IEC 60332-1 IEC 61034
-----------------------	--------------------------

## construction

Central strength member	FRP (for fiber count > 24F strand sub-unit structure)
Wrapping	Polyester (for fiber count >24F strand sub-unit structure)
Inner sheath	Subunit sheath is PVC or LSZH (for fiber count >24F)
Outer sheath	LSZH or PVC Riser

## mechanical properties

Tensile strength (<12 fibers)	Installation: 660 N Long Term: 165 N
Tensile strength (>12 Fibers)	Installation: 1300 N Long Term: 330 N
Compressive strength (crush)	350 N (2 fiber) 500 N (4F-12F, 24F singlepass) 1000 N (>24 strand sub-unit structure)
Impact	2.9 Nm
Torsion	100 N, +/- 180°, 10 cycles
Kink	R = 20 x OD
Temperature range	Shipping and Storage: -40°C to +70°C Installation: -20°C to +70°C Operation: -20°C to +70°C

# Opti-Core™ Fiber Optic Indoor Cable – Asia Pacific

## physical properties

Fiber Count	Cable O.D. (mm)	Installation Bend Radius (mm)	Long-Term Bend Radius (mm)	Cable Weight (kg/km)
2	2.9	58	29	14(LSZH)/14(Riser)
4	4.8	96	48	20 (LSZH)/19(Riser)
6	4.8	96	48	22(LSZH)/21(Riser)
8	4.8	108	54	27(LSZH)/26(Riser)
12	6.2	124	62	33(LSZH)/32(Riser)
24	8.5	290	145	60(LSZH)/60(Riser)
48	18	360	180	245(LSZH)/237(Riser)

## fiber color code 4 to 24 fibers

Fiber color code	1 Blue	7 Red
	2 Orange	8 Black
	3 Green	9 Yellow
	4 Brown	10 Violet
	5 Grey	11 Pink
	6 White	12 Aqua

## ordering information

Example: FLDRZ12Y- Fiber, Indoor Unarmored, Riser Rated, OM4, 12-fiber

Character	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>	<b>8</b>
Example	<b>F</b>	<b>L</b>	<b>D</b>	<b>R</b>	<b>Z</b>	<b>1</b>	<b>2</b>	<b>Y</b>

### 1 and 2 – Fiber Product

FL = Fiber OM1, OM2, OS2, OM3, OM4

### 3 – Cable Construction

I = Interconnect cable (2 & 4 fiber only)  
D = Indoor Distribution (6-48 fibers)

### 4 – Flame Rating

R - Riser  
L - Low Smoke Zero Halogen

### 5 – Fiber Type

9 = Singlemode (OS2 ITU G.652.D)  
6 = Multimode (OM1)  
5 = Multimode (OM2)  
X = Multimode (OM3)  
Z = Multimode (OM4)

### 6 and 7 – Fiber Count

02 = 2-Fiber  
04 = 4-Fiber  
06 = 6-Fiber  
08 = 8-Fiber  
12 = 12-Fiber  
24 = 24-Fiber  
48 = 48-Fiber

### 8 – RoHS Compliant

Y-Yes

## WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA  
Markham, Ontario  
cs-cdn@panduit.com  
Phone: 800.777.3300

PANDUIT EUROPE LTD.  
London, UK  
cs-emea@panduit.com  
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.  
Republic of Singapore  
cs-ap@panduit.com  
Phone: 65.6305.7575

PANDUIT JAPAN  
Tokyo, Japan  
cs-japan@panduit.com  
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA  
Guadalajara, Mexico  
cs-la@panduit.com  
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.  
Victoria, Australia  
cs-aus@panduit.com  
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)

For more information

Visit us at [www.panduit.com](http://www.panduit.com)

Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)  
or by phone: 800.777.3300

**PANDUIT™**

©2016 Panduit Corp.  
ALL RIGHTS RESERVED.  
FBDS19--WW-ENG  
7/2016